

A1 TILE SKIM

SKIM KOT SEGERA JUBIN | 瓷磚墙面膏




**UBAH DINDING BERJUBIN
KE DINDING BARU DENGAN
MUDAH DAN CEPAT!**

Skim Directly On Tiles



Skim secara terus di atas Jubin

No Mixing Required




Tidak perlu sebarang campuran

Reusable



Boleh diguna semula

Good Workability



Pemasangan yang mudah

Strong Adhesion



Daya lekatan yang kuat

A1 TILE SKIM

TURN TILED WALLS INTO NEW WALLS INSTANTLY!

快速的将瓷砖墙变成新墙



A1 TILE SKIM (688) : NORMAL WHITE

SPECIFICATIONS :

Approx. Coverage : $\pm 8\text{ft}^2 / 2\text{ layers/kg}$

Color : White

Thickness : 1-2 mm / layer

Usage : For shallow grout lines

Size : 10KG / 20KG



A1 TILE SKIM (678) : THICK WHITE

SPECIFICATIONS :

Approx. Coverage : $\pm 6\text{ft}^2 / 2\text{ layers/kg}$

Color : White

Thickness : 2-3 mm / layer

Usage : For deeper grout lines

Size : 10KG / 20KG

APPLICATION INSTRUCTIONS

1.



Tools Preparation

The basic tools to prepare are masking tape, hawk, trowel, spatula and fiber mesh.

2.



Surface Preparation

Make sure the surface is clean, free of dust, oil, flaking, cracks, holes, or other damages. Tape the sides of the surface with masking tape to make sure edges are clean and straight. The surface must be dry before applying A1 Tile Skim.

3.



First Layer

Apply first layer with trowel. Apply A1 Tile Skim evenly to cover all tile grout lines and surfaces. While its wet, incorporate fiber mesh into the first layer, and apply more material to cover the fiber mesh. We recommend using fiber mesh with 3mm x 3mm mesh size. Avoid overlapping the fiber mesh.

4.



Second Layer

Make sure the first layer is completely dry before applying the second layer. Apply the second layer to make the surface even, totally covering all grout lines. Wait for second layer to dry. Use sand paper to smoothen uneven surface if needed.



Storage

Keep package tightly closed and at room temperature.

Add ¼" water to the top of wet plaster to prevent drying out when planning to store for longer than 6 months .



f CAOMALAYSIA

CAO Industries Sdn. Bhd. (187571-K)
Lot 799, Batu 22, Jalan Ipoh,
48200 Serendah, Selangor, Malaysia.
www.cao.com.my
03 - 60919227
salesenquiry@cao.com.my

Available in :

